



## Properly Packing Bearings

<b>Brand</b>	BXT	<b>Product</b>	Bearings	<b>Date</b>	June 2020
<b>Part Number(s)</b>	Multiple				



**Issue:** Premature failure of serviceable bearing due to incorrect amount of grease.

Serviceable bearings require the correct type and amount of grease. An insufficient amount of grease may lead to overheating and rapid wear due to inadequate lubrication. Conversely, an excess amount of grease may cause leaching (grease escaping and damaging the external seal) and churn, leading to excessive operating temperatures and a breakdown of grease due to insufficient heat dissipation.



### Solution

Using a bearing packer tool filled with the correct type of grease (NLGI #2) will ensure that the appropriate amount of grease is evenly injected. Prevent contaminants from entering bearing assembly or packer tool. Bearing assembly should be approximately 1/3 to 1/2 filled with grease.

1. Place bearing assembly into packer tool.
2. Operate packer tool according to instructions. This will inject grease between rolling elements, races and cage.
3. Coat rolling elements and outer race with any excess grease.

Properly packing bearings will assist in extending component service life and prevent premature failure.



Technical Support Hotline: [1.844.572.1304](tel:1.844.572.1304)



For parts go to: [mevotech.com](http://mevotech.com)

Publication Number: MI-20-022-03-01-E



WE SUPPORT  
ASE CERTIFICATION

DISCLAIMER: The information in this communication is intended for use only by skilled technicians who have the proper tools, equipment and training to correctly and safely maintain vehicles. Refer to original manufacturers service manual for proper torque specifications and removal/installation procedures. All content in the publication is provided as-is and without warranty. All care has been taken to ensure the accuracy of the information presented. The publisher assumes no responsibility or liability for any loss or damage, direct, indirect or consequential, arising from the use of the information contained herein.