Improved Ease of Installation: 2022-2007 Nissan Sedan, Hatchback and Compact Van Front Lower Ball Joint

Brand	Supreme	Product	Ball Joint	Date	March 2023
Part Number(s)	MS30503				

Mevotech Supreme front lower ball joint MS30503 for the below noted applications is engineered with several enhancements to facilitate ease of install for the Professional Technician.

Application(s)

2018-2015 Chevrolet Express
2013-2009 Nissan Cube
2017-2011 Nissan Juke
2022-2011 Nissan LEAF
2019-2013 Nissan NV200
2019-2007 Nissan Sentra
2011-2007 Nissan Versa

MS30503 is designed with a significantly larger housing flange, both in diameter and thickness. This increases total surface area for press-in and allows the Professional Technician to utilize a wider range of adaptors. The larger flange improves part strength and knurling on the housing helps to seat the ball joint into the control arm bore. **See Figure 1**.

Additionally, new anti-corrosion coated hardware in the box allows for a complete and frustration-free install. **See Figure 2**.

MS30503 also features greaseable self-lubricating sintered bearings for optimized part service life.

WE SUPPORT ASE CERTIFICATION

DISCLAIMER: The information in this communication is intended for use only by skilled technicians who have the proper tools, equipment and training to correctly and safely maintain vehicles. Refer to original manufacturers service manual for proper torque specifications and removal/installation procedures. All content in the publication is provided as-is and without warranty. All care has been taken to ensure the accuracy of the information presented. The publisher assumes no responsibility or liability for any loss or damage, direct, indirect or consequential, arising from the use of the information contained herein.

MEVOTECH

X-FACTOR BULLETIN

Improved Ease of Installation: 2022-2007 Nissan Sedan, Hatchback and Compact Van Front Lower Ball Joint



Figure 1. Mevotech Supreme front lower ball joint MS30503 is engineered with a larger diameter and thicker flange and knurled housing when compared to an OE-style ball joint



Figure 2. New anti-corrosion coated fastening hardware is provided for a complete install

DISCLAIMER: The information in this communication is intended for use only by skilled technicians who have the proper tools, equipment and training to correctly and safely maintain vehicles. Refer to original manufacturers service manual for proper torque specifications and removal/installation procedures. All content in the publication is provided as-is and without warranty. All care has been taken to ensure the accuracy of the information presented. The publisher assumes no responsibility or liability for any loss or damage, direct, indirect or consequential, arising from the use of the information contained herein.